

Each Mini sprinkler assembly consist of mini sprinkler with an in-built stake, which can be attached to 12 or 16mm lateral. Also comes without stake, for which mini sprinkler can be belted to an external wooden/ metal stake of any suitable height.

Advantages:

- Can be connected to 12mm or 16mm drip laterals.
- Easy to disassemble and clean.
- Operates at low pressure
- Uniform wetting
- Cheaper to install than the conventional sprinkler system
Made from best quality polyacetal resin to give maximum life.
- Durable and unbreakable
- More durable than the micro sprinkler systems but need 2kg/cm² pressure as against 1.2 kgs/cms² required for micro sprinklers
- Reasonable pricing.



Application

- Minisprinkler systems are used where complete area is to be covered perfectly without causing any harm to the crop/plants.
- This is best suitable for all crops where it is necessary to cover entire area, like ginger, safedmusli, onions and medicinal plants and all vegetable plantations and nurseries.

Types available	Micro sprayer with tubing. Stake is optional
Operating pressure	1.5-2.5kg/cm ²
Emission rate from each nozzle	450lph at 2kg/cm ²
Wetting radius	6.5mtr at 2kg/cm ²
Maximum coverage	90% at 2kg/cm ²
Manufactured from	Polyacetal resin